

Sure-Trac Trailer

MINI-DERRICK SUPER 6000 LOW PRO

SKYLIFT

440-960-2100 | SKYLIFTUS.COM

Trailer Specifications - 20' 20,000 LB. G.V.W.R.

Total Length:	26'
Total Width:	8' 2"
Front Deck:	84" long x 72" wide with 2" x 6" pressure treated wood deck
Empty Weight:	3,340 LBS.
Cargo Deck:	114" long x 67.5" wide with 2" x 6" pressure treated wood deck
Tongue Length:	6'
Dovetail:	40" long with 6 degree slope
Axle:	(2) Two 10K oil bath slipper spring axles with electric brakes – 67.5" spring centers and 89.5" hub face
Tires:	(4) 215/75R-17.5
Safety Chain:	3/8" grade 70 – 36" overall length
Lights:	Rubber mounted sealed LED
Wiring:	Sealed wire harness
Brake/Battery:	Breakaway switch / LED battery box
Pintle Eye:	21 ton 3" pintle ring with vertical adjustment of 18" to 32"
Trailer Jack:	12K drop leg jack
Ramps:	Spring assist ramps – 20" x 60"
Tool Box:	Tongue mounted 48"W x 19"D x 17"H



SURE-TRAC

 **Novae**[®]